

Approximate Capacities at Various Pressures						
Rated Flow at 100 P.S.I.		Kg/h				
		Pressure BAR				
G.P.H.	l/h	10	12	14	18	20
0.40	1,51	1.59	1.74	1.88	2.13	2.25
0.45	1,70	1.76	1.93	2.08	2.36	2.49
0.50	1,89	1.91	2.09	2.26	2.56	2.70
0.55	2,08	2.12	2.32	2.51	2.84	3.00
0.60	2,27	2.36	2.59	2.79	3.17	3.34
0.65	2,46	2.59	2.84	3.06	3.47	3.66
0.75	2,84	2.89	3.17	3.42	3.88	4.09
0.85	3,22	3.31	3.63	3.92	4.44	4.68
0.90	3,41	3.57	3.91	4.22	4.79	5.05
1.00	3,78	3.73	4.09	4.41	5.00	5.28
1.10	4,16	4.33	4.74	5.12	5.81	6.12
1.20	4,54	4.63	5.07	5.48	6.21	6.55
1.25	4,73	4.83	5.29	5.71	6.48	6.83
1.35	5,11	5.19	5.69	6.14	6.96	7.34
1.50	5,68	5.78	6.33	6.84	7.75	8.18
1.65	6,25	6.36	6.97	7.53	8.53	9.00
1.75	6,62	6.74	7.38	7.97	9.04	9.53
2.00	7,60	7.66	8.39	9.06	10.28	10.83
2.25	8,50	8.61	9.43	10.19	11.55	12.18
2.50	9,50	9.57	10.48	11.32	12.84	13.54
2.75	10,4	10.53	11.53	12.46	14.13	14.89
3.00	11,4	11.49	12.59	13.59	15.42	16.25
3.50	13,0	13.40	14.68	15.85	17.98	18.95
4.00	15,0	15.31	16.77	18.11	20.54	21.65
4.50	17,0	17.23	18.87	20.39	23.12	24.37
5.00	19,0	19.14	20.97	22.65	25.68	27.07
5.50	21,0	21.06	23.07	24.92	28.25	29.79
6.00	23,0	22.97	25.16	27.18	30.82	32.49
6.50	25,0	24.89	27.26	29.45	33.39	35.20
7.00	26,5	26.8	29.36	31.71	35.96	37.91
7.50	28,0	28.71	31.45	33.97	38.52	40.61
8.00	30,0	30.63	33.55	36.24	41.09	43.32
9.00	34,0	34.46	37.75	40.77	46.23	48.74
10.00	38,0	38.28	41.93	45.29	51.36	54.14
11.00	42,0	42.11	46.13	49.82	56.50	59.56
12.00	45,0	45.94	50.32	54.36	61.63	64.98
13.00	49,0	49.77	54.52	58.89	66.77	70.40
14.00	53,0	53.6	58.71	63.42	71.91	75.81
15.00	57,0	57.43	62.91	67.95	77.05	81.23
16.00	61,0	61.26	67.10	72.48	82.19	86.65
17.00	64,0	65.08	71.29	77.00	87.31	92.05
18.00	68,0	68.91	75.48	81.53	92.45	97.47
20.00	76,0	76.57	83.87	90.60	102.7	108.3
22.00	83,0	84.23	92.27	99.66	113	119.14
24.00	91,0	91.88	100.7	108.7	123.27	129.96
26.00	98,0	99.54	109.04	117.8	133.5	140.8
28.00	106	107.2	117.4	126.8	143.8	151.6

Oil Standards: 3.4 cst. viscosity, .84 density @ 20 C per EN 293